

Helping Customers Innovate, Improve & Grow

Table 1. Electrical Performance

Parameter	Symbol	Min.	Typ	Max	Units
Nominal Frequency	F_{NOM}	3.500		75.000	MHz
Mode		Fundamental, 3rd Overtone			
Operating Temperature Range	T_{OP}	0/70, -10/70, -20/70, -40/85			°C
Stability Over T_{OP}^1	F_{STAB}	±10		±100	ppm
Frequency Tolerance ²	F_{TOL}		±10		ppm
Load Capacitance	C_L	6		32	pF
Shunt Capacitance	C_o			5	pF
Drive Level			10	100	uW
Aging / 1st year (at 25 °C)	F_{AGE}			±5	ppm
Insulation Resistance		500			MOhm
Storage Temperature	T_{STO}	-40		90	°C
Equivalent Series Resistance					
Crystal Frequency	ESR				Ohm
3.500MHz-4.000MHz				140	
4.001MHz-5.000MHz				120	
5.001MHz-6.000MHz				80	
6.001MHz-7.000MHz				70	
7.001MHz-9.000MHz				45	
9.001MHz-13.000MHz				40	
13.001MHz-16.000MHz				35	
16.001MHz-20.000MHz				30	
20.001MHz-30.000MHz, Fundamental				25	
24.001MHz-32.000MHz, 3rd Overtone				120	
32.000MHz-80.000MHz, 3rd Overtone				80	

Notes:

1. Referenced to the Frequency at 25 °C.

2. Frequency measured at 25 °C ± 3 °C.

Product is compliant to RoHS directive and fully compatible with lead free assembly. 

Package Drawing

