


SOLDER PAD LAYOUT



Features

- ▣ Wide frequency range
- ▣ Low profile plastic moulded package

Specifications

Parameters	Product	Option Codes
	GSX-309	
Frequency range:	4.0 ~ 30.0MHz	■
Calibration tolerance:	±30ppm	□
	±50ppm	□
Temperature stability:	±30ppm	□
	±50ppm	■
Operating temperature range:	-10 to +60°C	■
	-40 to +85°C	□
	Other values	□
		1, 4, specify
Operable temperature range:	-40 to +85°C	■
Storage temperature range:	-55 to +125°C	■
Circuit condition:	16pF	■
	18pF	□
	20pF	□
	30pF	□
	Other values	□
Oscillation mode:	Fundamental	■
Static capacitance (C ₀):	5pF max	■
Equivalent series resistance (max):	150Ω (4.0 ~ 5.5MHz)	■
	100Ω (5.5 ~ 9.9MHz)	■
	60Ω (10.0 ~ 15.9MHz)	■
	40Ω (16.0 ~ 30.0MHz)	■
Ageing:	±5ppm max first year	■
Drive level:	100μW typ	■
Shock resistance:	±5ppm	■
Soldering conditions:		
	260°C, 10sec max	■

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + option codes + frequency

eg: **GSX-309/551DF 16.0MHz** 50/50/10/16-F (standard)

GSX-309/354JF 24.0MHz 30/50/40/30-F

Option code X (eg GSX-309/X) denotes a custom specification.

◆ Available on T&R - 1k pcs per reel.

◆ **WARNING** - Not recommended for new designs.