



A 47nF ceramic capacitor must be connected between GND and V_{DD}

Features

- ▮ Suitable for Avionics, Down-hole, Geothermal etc
- ▮ Extreme temperature ranges up to 200°C
- ▮ High stability & low ageing under extremes
- ▮ High shock & vibration resistance
- ▮ Low current consumption

Enable / Disable Function

Input (pad 1)	Output (pad 3)
Open	Enabled
'1' level	Enabled
'0' level	High Impedance

Reaction time <5ms

Specifications

Parameters	Product	Option Codes
	MCSO1EL	
Frequency range:	32.768kHz 10.0 ~ 50.0kHz	■ □ specify
Supply voltage (V _{DD}):	+5.0V (±5%) +3.3V (±5%) +2.5V (±5%)	■ □ □ V W
Frequency stability (max)*:	±100ppm over -55 to +125°C ±150ppm over -55 to +150°C ±300ppm over -55 to +175°C ±400ppm over -55 to +200°C (Option G only available at 5V)	□ □ □ □ G
Storage temperature range:	-65 to +125°C	■
Supply current (max @ 10pF load):	120µA, V _{DD} =5.0V 110µA, V _{DD} =3.3V 100µA, V _{DD} =2.5V	■ ■ ■
Driving ability:	CMOS	■
Load:	3pF min, 27pF max	■
Logic levels:	'0' level = +0.4V max '1' level = V _{DD} -0.5V min	■ ■
Start up time:	5ms max	■
Waveform symmetry:	40:60 max @ 50%V _{DD}	■
Rise / fall times:	25ns max (15pF, 20%~80%)	■
Enable / disable function:	None (pad 1 NC) Tristate (control via pad 1)	■ □ E
Standby current:	5µA max	■
Shock resistance:	10,000G, 0.3ms, ½ sine	■
Vibration resistance:	40G rms 10.0 ~ 2,000Hz	■
Soldering condition:	260°C, 10 sec max	■
Terminations:	Gold plated pads Tinned pads* (Ag/Cu/Zn)	■ □ T

■ Standard. □ Optional - Please specify required code(s) when ordering

* Frequency stability is inclusive of calibration @ 25°C, operating temperature range, supply voltage change, load change and long term ageing (1,000hrs at T_{MAX}).

Ordering Information

Product name + option codes + frequency

eg: **MCSO1EL/DE 32.768kHz** 5V ±300ppm -55 to +175°C Enable / disable

MCSO1EL/WD 32.768kHz 2.5V ±300ppm -55 to +175°C no E/D

Option code X (eg MCSO1EL/X) denotes a custom specification.

◆ Packed in trays (91pcs/tray), or T&R 250 ~ 1,000pcs / reel