



actual size

Oscillator · (VC)TCXO · JT33(V)

Temp. Compensated Crystal Oscillator · 3.2 x 2.5 mm

- low power VCTCXO or TCXO
- temperature range -40 °C ~ +85 °C available
- reflow soldering temperature: 260 °C max.
- ceramic/metal package



General Data

type		JT33 / JT33V
frequency range		8.0 ~ 52.0 MHz
frequency	at +25 °C	± 1.5 ppm (incl. 2x reflow)
	tolerance/temperature	± 1 ppm ~ ± 5 ppm (table 1)
	stability/aging first year	± 1 ppm
	supply voltage	± 0.2 ppm (at $V_{DC} \pm 5\%$)
load change		± 0.2 ppm
current consumption		2.5 mA max.
supply voltage V_{DC}		1.8 / 2.5 / 2.8 / 3.0 / 3.3 ($\pm 5\%$)
temperature	operating	see table 1
	storage	-40 °C ~ +85 °C
output	load nom.	10 K Ω // 10 pF
	level min.	0.8 Vpp (clipped sine)
external tuning range JT33V		± 8 ppm min.
external tuning voltage JT33V		0.9 V \pm 0.9 V at $V_{DC} = 1.8$ V (standard) 1.5 V \pm 1.0 V at $V_{DC} \geq 2.5$ V (standard) 1.4 V \pm 1.0 V at $V_{DC} \geq 2.5$ V (option)
start-up time max.		2.5 ms
phase noise	at 100 Hz	-109 dBc/Hz typ.
	at f_o	-133 dBc/Hz typ.
26 MHz	at 10 KHz	-148 dBc/Hz typ.

Table 1: Frequency Stability vs. Temperature

operating temperature code	frequency stability code					
	Y	Z	A	B	C	D
Y : ± 5.0 ppm						
Z : ± 3.0 ppm						
A : ± 2.5 ppm						
B : ± 2.0 ppm						
C : ± 1.5 ppm						
D : ± 1.0 ppm						
A : -30 °C ~ +80 °C	○	○	○	○	○	○
B : -20 °C ~ +70 °C	○	○	○	○	○	○
C : -10 °C ~ +60 °C	○	○	○	○	○	○
D : 0 °C ~ +85 °C	○	○	○	○	○	○
E : 0 °C ~ +55 °C	○	○	○	○	○	○
F : -10 °C ~ +70 °C	○	○	○	○	○	○
G : -30 °C ~ +75 °C	○	○	○	○	○	○
H : -20 °C ~ +75 °C	○	○	○	○	○	○
K : -40 °C ~ +85 °C	○	○	○	○	○	○
L : -20 °C ~ +85 °C	○	○	○	○	○	○
M : -30 °C ~ +85 °C	○	○	○	○	○	○

● standard ○ on request

Note

- TCXO JT33: pin #1 connected to GND
- VCTCXO JT33V: pin #1 is control voltage V_c
- external AC coupling for output recommended

Dimensions

top view

side view

bottom view

pad layout

TCXO JT33	VCTCXO JT33V
# 1: GND	# 1: Vcontrol
# 2: GND	# 2: GND
# 3: output	# 3: output
# 4: Vdc	# 4: Vdc

pin connection

in mm

Order Information

0	frequency in MHz	type	frequency stability code	operating temp. code	supply voltage	control voltage (for JT33V only)
Oscillator	8.0 ~ 45.0 MHz	JT33 = TCXO JT33V = VCTCXO	A - Z see table 1	A - K see table 1	1.8 = 1.8 V 2.5 = 2.5 V 2.8 = 2.8 V 3.0 = 3.0 V 3.3 = 3.3 V	0.9 = V_c 0.9 V \pm 0.9 V at $V_{DC} = 1.8$ V 1.5 = V_c 1.5 V \pm 1.0 V at $V_{DC} \geq 2.5$ V 1.4 = V_c 1.4 V \pm 1.0 V at $V_{DC} \geq 2.5$ V see General Data

Example: O 26.0-JT33V-A-G-3.3-1.5-LF (Suffix LF = RoHS compliant / Pb free pads)

