

- ▶ Compact and low profile
- ▶ Industry Std. Footprint
- ▶ Extended Temp Range Option
- ▶ RoHS Compliant
- ▶ 6 x 3.5 mm (2 Pad)
- ▶ MSL 1
- ▶ Lead Finish: Au

ECX-64A

SMD QUARTZ CRYSTAL

The ECX-64A is a miniature SMD Crystal with a 3.5 x 6 mm 2 pad footprint. This cost effective with a height of 1.1 mm which is ideal for densely populated PCB applications.

OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

PARAMETERS	CONDITIONS	ECX-64			UNITS
		MIN	TYP	MAX	
Frequency Range		8.000		100.00	MHz
Frequency Tolerance	at +25°C			± 30 *	ppm
Frequency Stability	-10 to +70°C			± 50 *	ppm
Shunt Capacitance				7	pF
Load Capacitance	Specify in P/N	10	20	Series	pF
Drive Level				100	μW
Operating Temperature *		-10		+70	°C
Storage Temperature		-55		+125	°C
Aging (Per Year)	@ +25°C ±3°C			±5	ppm

EQUIVALENT SERIES RESISTANCE/MODE OF OSCILLATION

FREQUENCY RANGE (MHz)	MODE OF OSC	MAX ESR Ω	FREQUENCY RANGE (MHz)	MODE OF OSC	MAX ESR Ω
8.000 ~ 15.999	Fundamental	80	20.000 ~ 49.999	Fundamental	30
16.000 ~ 19.999	Fundamental	60	50.000 ~ 100.000	3rd Overtone	100

DIMENSIONS (mm)




Figure 1) Top, Side, and Bottom views




Figure 2) Suggested Land Pattern

PART NUMBERING GUIDE: Example ECS-200-20-23A-TR

Custom Options